

**TORO**

# Multi Pro<sup>®</sup> 5800

## 300-Gallon Sprayer

## LEADING TECHNOLOGY, PROVEN RELIABILITY, UNSURPASSED ACCURACY.

The Multi Pro 5800 is just what you would expect from the market leader in turf sprayers. We took hundreds of hours of insightful customer input and created the most advanced spray system on the market. Virtually every aspect of the spray system has been optimized for performance accuracy. We have engineered in aggressive agitation and faster response times to consistently and accurately apply desired spray rates. Extensive testing and reliable components ensure the Multi Pro 5800 is ready to perform when you need it most. Add highly productive work attachments and accessory kits to save labor and chemical costs by simplifying the mixing and spraying processes. Contact your Toro distributor to learn more, or schedule a demonstration on your course.



[toro.com/multipro](https://toro.com/multipro)

## F E A T U R E S

### Six Diaphragm Pump

- An industry exclusive – this oversized pump satisfies the highest spray rates while simultaneously supplying generous agitation flow.

### 300 gal (1,136 L) Chemical Tank

- Ready for the long haul, this thoughtfully designed tank incorporates four, 30 degree, side-mounted agitation nozzles to ensure homogeneous mixing of chemicals for application consistency and accuracy. Polyethylene material won't crack, dent, rust, chip or peel.

### Powerful Kubota<sup>®</sup> Engine

- Proven 50 hp (37.3 kW) liquid-cooled EFI gasoline engine has the power to perform in the most demanding conditions.

### Rugged Triangular Spray Boom

- Three section, 20.5' (6.25 m) boom width provides fore and aft breakaway on impact while protecting nozzles. Raises into a crisscross position for storage and transportation.

### Center Control Console

- With Quick Find<sup>™</sup> armrest & LCD InfoCenter display featuring ExcelaRate<sup>™</sup> automatic spray application rate control.

MULTI PRO 5800-G, MODEL 41394	
<b>ENGINE</b>	Kubota® WG1605, rated output: 50 hp (37.3 kW), 1.6 L, 4-cylinder liquid-cooled electronic fuel injection, throttle control, three-way catalytic converter, gear-driven valve train, and a diagnostic port.
<b>COOLING SYSTEM</b>	Mid-mounted 3.3 (3.12 L) quart radiator with oil cooler mounted in front.
<b>FUEL SYSTEM</b>	12 gallon (45 L) polyethylene/Nylon low-permeation fuel tank with 1.5" (38 mm) opening on the passenger side for fueling; 3.5 psi vented fuel cap with electronic fuel gauge on the console, in-tank fuel replacement filter, (unleaded gasoline).
<b>TRACTION SYSTEM</b>	Hydrostatic system driving double planetary gear reduction rear wheel drives; foot pedal control of forward/reverse ground speed.
<b>GROUND SPEED/CLEARANCE</b>	Forward: 0-10 mph (0-16.1 km/h). Reverse: 0-4 mph (0-6.4 km/h).
<b>TIRES</b>	Front: 23" diameter rounded profile, 4-ply rated tire with smooth tread pattern; wheel has 5-hole bolt pattern for lugs. Rear: 26.5" diameter rounded profile, 6-ply rated tire with turf tread pattern; wheel has 8-hole bolt pattern for lugs.
<b>BRAKES</b>	2-wheel mechanical cable operated multi disc wet brakes with additional hydrostatic braking through drive train.
<b>MAIN FRAME</b>	Welded high strength steel tubular construction.
<b>SUSPENSION</b>	Front: straight axle with twin independent leaf springs and dual shock absorbers. Rear: rigid with high flotation rear tires.
<b>STEERING</b>	Fully hydraulic with dedicated power source 48° steering angle.
<b>GAUGES/INDICATORS</b>	Ignition key switch; analog spray system pressure gauge; fuel gauge; battery voltage lamp; oil pressure warning lamp; coolant temperature warning lamp; InfoCenter display console.
<b>CONTROLS</b>	Throttle control; spray pump switch; tank agitation switch; individual boom section switches; master boom switch; speed-lock switch; manual/automatic spray mode switch; boom lift/lower switches; manual application rate control (pressure) switch; USB port; 12V power socket; ExcelaRate™ automatic spray rate control (via InfoCenter).
<b>SEATS</b>	Bucket seats with easy tilt forward bracket; removable bolts allow for adjustment for various seat positions; seats are interchangeable from left to right.
<b>ELECTRICAL FEATURES</b>	12 volt, 690 cold cranking amps at 0° F (-18° C). 12 volt, 60 Amp alternator. Dash mounted ignition switch, with glow plug timing circuit.
<b>LIGHTS</b>	Rectangular 12 volt, 37.5 watt halogen sealed beam headlights.
<b>SOUND LEVEL</b>	90 dB(A) at operator ear under normal operation
<b>WEIGHT</b>	Drive-on weight: 2,882 lbs. (1,307 kg), Shipping weight: 2,882 lbs. (1,307 kg), Empty vehicle: 2,882 lbs. (1,307 kg), Full w/ Operator: 5,692 lbs. (2,582 kg), MGWV: 6,692 lbs. (3,035 kg).
<b>DIMENSIONS</b>	Measurements with spray system— Overall Length: 154" (391 cm) booms forward. Turning Diameter: 15'-7" (4.7 m) front tire inside Overall Width: 88" (224 cm) booms forward.. 26'-7" (8.1 m) front tire outside Height: 57.5" (146 cm)
<b>WARRANTY</b>	Two-year limited warranty. Refer to the Operator's Manual for further details.
<b>CERTIFICATION</b>	SAE 2258 Dec. 2003 and EU 98/37EC Machinery Directive. 2014/108/EC (EMC).

SPRAYER SPECIFICATIONS	
<b>SOLUTION TANK</b>	Elliptical, high-density, impact-resistant polyethylene with large 16" (41 cm) fill well.
<b>RATED CAPACITY</b>	300 gallon (1,136 liter).
<b>SPRAY PUMP</b>	Hardi 364 / 10.0 6-diaphragm positive displacement; flow rate 45 gpm (170.3 lpm), 220 psi (1500 kpa) maximums.
<b>AGITATOR</b>	4, side-mounted jet agitation nozzles for full tank agitation.
<b>BOOM ASSEMBLY</b>	20.5' (6.25 m), 4 nozzles per selection, triangular truss-style open boom. 12 total triple-turret nozzle mounts with diaphragm check valves.

**A Safety Reminder:** Prior to any application, know the chemical content and the manufacturer's recommendation for protective clothing. Always wear proper clothing and mask when applying chemicals.

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



MULTI PRO 5800 ACCESSORIES	
<b>CLEANLOAD EDUCTOR KIT</b>	This on-board mixing station allows rapid and safe loading of any chemical without the need to first mix into a slurry. Incorporates a built-in bottle wash feature and has an optional suction lance to draw liquid or powder products from their container. Stores within the width of the spray vehicle for transport.
<b>FRESH WATER RINSE KIT</b>	30 Gallons (114 L). Nesting inconspicuously behind the main tank, this system includes a separate electric diaphragm pump, dedicated plumbing and dual rinse nozzles. At 10 gallons (38 L) per cycle, it has on-board capacity to complete a triple rinse process, saving precious time.
<b>ELECTRIC HOSE REEL KIT</b>	150' (45.7 m) of 0.5" (13 mm) hose for hand or walk spraying applications. Convenient electric powered rewind. Spray gun has an adjustable nozzle from stream to fan.
<b>PRO FOAM MARKING KIT</b>	Foam dollops ensure accurate parallel path tracking. Select foam for either boom or both.
<b>PRO FOAM</b>	1 gallon (3.8 L) bottle of Pro Foam Concentrate.
<b>HAND SPRAY WAND KIT</b>	Spray manually using handheld device for precision and accuracy.
<b>ULTRA SONIC BOOM LEVELING KIT</b>	Sonar sensors automatically maintain proper boom height over undulating turf for consistent and proper spray pattern.
<b>DRIFT REDUCTION BOOM SHROUD</b>	Extends 12" (30.5 cm) below the boom to minimize chemical drift in breezy conditions while retaining full boom system functionality.
<b>SUNSHADE</b>	Hard shell sunshade canopy w/windshield option. (From Custom Products of Litchfield, 1-800-CAB-LINE, www.cozycab.com/cabs).
<b>FULLY ENCLOSED CAB</b>	Full-view operator safety cab with AC, wiper and mirror options. (From Custom Products of Litchfield, 1-800-CAB-LINE, www.cozycab.com/cabs).
<b>AIR CONDITIONER</b>	Custom Products of Litchfield, 1-800-CAB-LINE, www.cozycab.com/cabs.
<b>CONTACT &amp; SYSTEMIC NOZZLES</b>	Select the right nozzle for your application by using the <b>Toro Nozzle Selector</b> - available via Toro.com

**A Safety Reminder:** Prior to any application, know the chemical content and the manufacturer's recommendation for protective clothing. Always wear proper clothing and mask when applying chemicals.

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Rev. 1/19

The Multi Pro 5800 is manufactured in Tomah, WI ISO 9002 Certified Plant.



**toro.com**

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801

©2019 The Toro Company.  
All Rights Reserved.  
19-243-GB



facebook.com  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope



**Count on it.**