

TORO

Z Master® 2000

Zero Turn Mower

THE Z MASTER 2000 REALLY SHINES WITH COMMERCIAL PERFORMANCE, RELIABILITY AND EFFICIENCY AT AN UNBEATABLE VALUE.

Finish more jobs faster than ever with the powerful engines and upgraded hydros, and it's built to take on the toughest hits with a fully tubular frame, large 61 cm rear tyres and 7/10-gauge steel deck with bullnose bumper.

World-class comfort with MyRide, built-in lights, and your customers will love the beautiful cut of the TURBO FORCE® deck.



toro.com

Powered by
Kawasaki



FEATURES

Power & Durability

- Powerful Kawasaki EU Stage V compliant engines
- Fully tubular frame and rugged 7-gauge TURBO FORCE® decks
- Available 122 cm (48") or 132 cm (52") width of cut.

Performance

- 74456TE - 19,500 m²/h* (4.8 acres/hr)
- 77292TE - 21,500 m²/h* (5.3 acres/hr)

Productivity

- Up to 13 km/h (8 mph) ground speed**
- 3,8-12,7 cm (1.5-5") height of cut with the standard mechanical Height of Cut foot pedal
- MyRIDE® suspension system

Versatility

- Quick Carry System Triple Threat utility kit. Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit, Universal Mount and Trimmer Mount. Sold separately.

*Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.

	74456TE HDX MyRIDE®	77292TE HDX MyRIDE
POWER SYSTEM		
ENGINE*	Kawasaki FX730V 17,5 kW (23,5 cv) 726 cc	Kawasaki FX730V 17,5 kW (23,5 cv) 726 cc
STARTER	Electric	Electric
HEAVY-DUTY DONALDSON®CANISTER AIR CLEANER	Standard	Standard
DRIVE TYRES	Hoosier Turf Tyres - Standard 22 x 9.5-12	Hoosier Turf Tyres - Standard 22 x 9.5-12
CASTER TYRES	Black Pneumatic 13 x 6.5-6	Black Pneumatic 13 x 6.5-6
FUEL/CAPACITY	Petrol 26,5 L (7 gal)	Petrol 26,5 L (7 gal)
DIGITAL HOUR METER	Standard	Standard
HYDRAULIC DRIVE SYSTEM	Integrated Pumps & Wheel Motors	Integrated Pumps & Wheel Motors
GROUND SPEED	13 km/h (8 mph)	11 km/h (7 mph)
MOWING DECKS		
DECK SIZE	122cm (48")	132cm (52")
DECK CONSTRUCTION	7/10-ga TURBO FORCE®, Rear Discharge	7/10-ga TURBO FORCE®, Side Discharge
BULLNOSE BUMPER	Standard	Standard
RUBBER DISCHARGE CHUTE	N/A	Standard
SPINDLE ASSEMBLIES	20,3 cm (8") Diameter Cast Aluminium	20,3 cm (8") Diameter Cast Aluminium
HEIGHT OF CUT	3,8-12,7cm (1.5-5"), 0,64 cm (0.25") increments	3,8-12,7cm (1.5-5"), 0,64 cm (0.25") increments
HEIGHT OF CUT FOOT PEDAL	Standard, Mechanical	Standard, Mechanical
DECK DEPTH	12,7 cm (5")	12,7 cm (5")
BLADES	3 Blades, 0.52 cm (0.204")	3 Blades, 0.52 cm (0.204")
FEATURES		
MyRIDE® SUSPENSION SYSTEM	Yes	Yes
SHOCKS	1 center / 2 rear	1 center / 2 rear
SEAT	Deluxe w/ Armrests	Deluxe w/ Armrests
STEERING CONTROLS	3,6 cm (1.4") Diameter Grips; Adjustable, Dampened	3,6 cm (1.4") Diameter Grips; Adjustable, Dampened
ROPS	Round Tube	Round Tube
ACCEPTS QUICK-ATTACH ACCESSORIES	Yes	Yes
LED LIGHTS	Optional	Optional
WEIGHT & MEASUREMENTS		
WEIGHT¹	432 kg (953 lbs)	474 kg (1046 lbs)
ROPS HEIGHT (UPRIGHT)	179,1 cm (70.5")	179,1 cm (70.5")
ROPS HEIGHT (FOLDED)	124,5 cm (49")	124,5 cm (49")
WIDTH (DEFLECTOR DOWN)	NA	170 cm (67")
WIDTH (DEFLECTOR UP)	NA	144,1 cm (56.75")
LENGTH	208,3 cm (82")	208,3 cm (82")
TIER 4 FINAL/STAGE V EMISSION COMPLIANT	Yes	Yes
WARRANTY	4-Years or 750 hours. ² 3-Year Limited Warranty for Engine. ³	
ACCESSORIES	136-9047 Triple Threat Kit (includes bucket holder, universal mount, and trimmer mount); 136-9046 Universal mount kit; 136-1654 Bucket Mount Kit; 136-1682 Trimmer Mount Kit; 133-2533 Toro 5 Gallon (18.9 L) Bucket; 136-1683 ROPS Pin Kit; 490-7319 Toro Deluxe Rider Cover; 127-6666 Jack Kit; 127-6794 MVP Belt & Blade Kit, 132 cm; 126-7882 Striping Kit, 132 cm; 126-8077 Sunshade; 126-5382 LED Light Kit	

* The gross horsepower of these engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

¹ Net Weight – machine without fuel

² Whichever occurs first

³ Some products used on Toro LCE Products are warranted by the engine manufacturer.

toro.com

©2020 The Toro Company.
All Rights Reserved.
20-611-GB

Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

