

FLEX-FORCE POWER SYSTEM™

60V* BATTERY LINE

EASY⚡ POWER


Get more done and enjoy more free-time with the Toro® 60V* Flex-Force Power System™. Toro's legendary reliability, durability and performance, now available with the benefits of battery power. Finally, a cordless platform without compromises.

Battery String Trimmer

Adjust this trimmer for any job with the variable speed trigger and two speed ranges, or by adjusting line size and/or cutting width – no spools required!



* Available 2020.



COMPACT POWER

Perfect for hand tools.
L135 Battery (2.5 Ah; 135 Wh)

EASY TO USE



EASY TO START



Battery Leaf Blower

Take charge of yard clean-up with the 60V Max* Battery Leaf Blower. Control is at your fingertips with the variable-speed trigger, turbo-boost button, and cruise control.



VERSATILE POWER

Easily mow a small to medium garden, with power to spare for trimming and blowing.
L324 Battery (6.0 Ah; 324 Wh)

EASY TO MAINTAIN



55 cm Recycler® Battery Mower

Save time, finish faster, and make your job easier with this easy-to-start, easy-to-use, and easy-to-maintain mower.



HEAVY DUTY POWER

Mow a large garden and get extended power for trimming and blowing.
L405 Battery (7.5 Ah; 405 Wh)

* Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

60V MAX* | FLEX-FORCE POWER SYSTEM™

EASY ⚡ POWER



A BATTERY FOR ANY APPLICATION
3 battery options to choose from.



GUARANTEED PEACE OF MIND
Toro stands behind its products with a full 3-Year Warranty on Equipment and Battery***

BATTERY LEAF BLOWER 51825T

MOTOR	Brushless DC	
FLEX-FORCE POWER SYSTEM™ BATTERY AND CHARGER	Battery and charger sold separately 60V 2.5 Ah; 135 Wh Recommended	
RUN-TIME*	SPEED SETTING	
	Low	Up to 90 min
	High	Up to 25 min
	Turbo Boost	Up to 10 min
SPEED CONTROL	Variable trigger, Turbo Boost	
WEIGHT (With 2.5 Ah 135 Wh battery)	3.4 Kg	
AIR VOLUME (m ³ /min**)	Up to 17 m ³ /min	
AIR SPEED (Km/h**)	Up to 185 Km/h	
NOISE RATING	Measured Sound Power: 101 dBA; Guaranteed Sound Power: 103 dBA; Sound Pressure: 86 dBA; K-factor: 3	
HAND / ARM VIBRATION	Left & Right: 1.5 m/s ² rms, Uncertainty K: 0.1 m/s ²	
COMFORT GRIP	Standard	

[^]Based on L135 battery at low speed in controlled laboratory testing of product.
^{**}Up to 17 m³/min Max and Up to 185 Km/h Max on turbo boost. Performance claims based on controlled laboratory testing.

BATTERY STRING TRIMMER 51835T

CUTTING WIDTH	36 cm - 41 cm		
MOTOR	Brushless DC		
FLEX-FORCE POWER SYSTEM BATTERY AND CHARGER	Battery and charger sold separately 60V 2.5 Ah; 135 Wh Recommended		
RUN TIME*	CUT LENGTH	LINE DIAMETER	RUN TIME*
	36 cm	2.0 mm	Up to 50 min
	36 cm	2.4 mm	Up to 45 min
	41 cm	2.4 mm	Up to 30 min
SPEED CONTROL	Variable trigger, 2 speed ranges		
WEIGHT (With 2.5 Ah 135 Wh battery)	4.58 Kg		
NOISE RATING	Measured Sound Power: 90 dBA; Guaranteed Sound Power: 93 dBA; Sound Pressure: 78 dBA; K-factor: 3		
HAND / ARM VIBRATION	Left & Right: 3.2 m/s ² rms, Uncertainty K: 0.8 m/s ²		
TRIMMER LINE	2.4 mm line included. 2.0 mm line sold separately.		
LINE ADVANCEMENT	Tap & Go. Standard		
QUICK-FEED HEAD	Standard		
COMFORT GRIP	Standard		

[^]Based on L135 battery, at low speed in controlled laboratory testing of product.

55 CM RECYCLER® BATTERY MOWER

MODEL	21863	21863T	
CUTTING WIDTH, HEIGHT	55 cm; 4 point, 25-102 mm		
MOTOR	2.0 kW Brushless DC		
FLEX-FORCE POWER SYSTEM BATTERY	L324 Battery Included 60V 6.0 Ah; 324 Wh	Sold Separately	
FLEX-FORCE POWER SYSTEM® CHARGER	Charger Included	Sold Separately	
TOTAL AREA CUT*	BATTERY	WATT HOURS/ CHARGE	TOTAL AREA CUT*
	L324 (6.0 Ah)	324	1300 m ²
	L405 (7.5 Ah)	405	1600 m ²
SPEED CONTROL	AutoMatic Drive System		
WEIGHT	36 Kg (With 6.0 Ah 324 Wh Battery)	33 Kg (Without Battery)	
DECK CONSTRUCTION	Steel		
GRASS BAG CAPACITY	74 L		
NOISE RATING	Measured Sound Power: 90 dBA; Guaranteed Sound Power: 91 dBA; Sound Pressure: 79 dBA; K-factor: 1		
NOISE/VIBRATION LEVELS	Left & Right: 0.3 m/s ² rms, Uncertainty K: 0.1 m/s ²		
RECYCLER/MULCHING	Standard		
RECYCLE ON DEMAND	Standard		
RUNSMART™	Standard		
SMARTSTOW®	Standard		

[^]Based on low speed in controlled laboratory testing of product.



facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



* Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.
***Refer to operator's manual or your local dealer for complete warranty information.

©2019 The Toro Company Part No. 200-xxxx
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties. toro.com