

## TAKE CHARGE OF YOUR WORKDAY.

For decades, the Toro Workman lineup has set the standard for tough and hard-working utility vehicles. Toro is proud to continue this legacy of performance with the all-new Workman MDX Lithium.

This lithium-powered MDX comes with same payload capacity, trailer towing capacity and comfortable ride that you have come to know in our gas and diesel-powered Workman MDX.



[toro.com](https://toro.com)

## F E A T U R E S

### Toro Hypercell™ batteries

- The lithium-powered MDX utilises Toro's patent-pending lithium-ion Hypercell batteries that provide extended battery power for consistent performance over the life of the vehicle. The MDX Lithium quickly charges overnight, keeping you running all day long.

### Superior comfort & control

- The proprietary SRQ™ (Superior Ride Quality) suspension creates a smooth ride and reduces rider fatigue, allowing your team to stay more productive throughout the day.
- MDX comes standard with an automotive-grade rack and pinion steering system, providing more control and lower steering effort. This allows operators to focus on the task at hand and move throughout your property more safely.

### Commercial grade durability

- Virtually unbreakable exterior components make the Workman MDX Lithium more durable and dependable. This vehicle is built to work as hard as you do, year after year.



WORKMAN MDX LITHIUM, MODEL 08303/08303TC	
<b>POWER SOURCE</b>	Lithium-ion batteries with integrated Battery Management System (BMS)
<b>CHARGER</b>	On-board high efficiency 1,200 W smart charger. -AC input voltage 100–240 VAC -AC input frequency 50/60 Hz -Max input current 13.4 A
<b>SRQ™ SYSTEM</b>	Active In-Frame™ twister pivot joint, front and rear suspension.
<b>FRONT SUSPENSION</b>	Modified MacPherson strut, adjustable coil-over shock absorbers.
<b>REAR SUSPENSION</b>	Trailing arm with adjustable coil-over shock absorbers.
<b>GROUND SPEED</b>	16 mph standard, adjustable from 5–19 mph
<b>BRAKES</b>	All-wheel hydraulic disc brakes. Integrated automatic parking brake.
<b>STEERING</b>	Rack and pinion steering system with ergonomic steering wheel that includes an intergrated clip.
<b>FRAME</b>	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat and powder coat finished. Body and bed constructed of dent- and corrosion-resistant polyethylene.
<b>GROUND CLEARANCE</b>	Front: 25.4 cm (10"), Rear: 18 cm (7")
<b>TYRES</b>	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply. Mounted on custom aluminium rims.
<b>DIMENSIONS</b>	Length/width 307.5 cm (121.1")/204.2 cm (80.4"). Wheel base 155.4 cm (61.2")
<b>CANOPY DIMENSIONS INSTALLED</b>	Height/width: 201.9 cm (79.5")/155.4 cm (61.2")
<b>TURNING CLEARANCE CIRCLE</b>	Inside rear tyre: 221 cm (87"), outside front tyre: 653 cm (257")
<b>INSTRUMENTATION</b>	Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch and parking brake lever. Two cup holders, radio holder, in-dash storage compartments, speedometer, gear indicator, estimated charge time and diagnostic/fault codes.
<b>STARTING</b>	Pedal start
<b>CARGO BED SIZE INTERNAL</b>	Length: 113 cm (44.5"), width: 125 cm (49"), height: 26 cm (10.25"), LLDPE resin
<b>TOTAL VEHICLE CAPACITY</b>	750 kg (1,650 lb)
<b>CARGO BED PAYLOAD CAPACITY</b>	567 kg (1,250 lb)
<b>TRAILER TOWING CAPACITY</b>	182 kg (400 lb) trailer, 23 kg (50 lb) tongue weight with standard hitch. 544 kg (1,200 lb) trailer, 45 kg (100 lb) tongue weight with heavy-duty tow hitch
<b>OPTIONAL ACCESSORIES</b>	Canopy, windscreen, electric bed lift, brush guard, ROPS, brake/tail/indicator light kit, receiver hitch, BOSS® plough
<b>WARRANTY</b>	Two-year or 1,500-hour warranty. Lithium-ion battery five years. Refer to the Operator's Manual for further details

## Power to get the job done.

Toro's proprietary Hypercell™ battery system was specifically developed to meet customer demand and is optimised to deliver exceptional continuous runtime, allowing it to run as long as your crew. At the end of a long workday, the on-board charger conveniently plugs into any standard power outlet and fully charges the vehicle overnight.



\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Rev. 2/23

The Workman MDX is manufactured in Tomah, WI ISO 9002 Certified Plant.



### toro.com

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801  
Fax: (1) 952 887 8258

©2023 The Toro Company.  
All rights reserved.  
23-246-GB



facebook.com  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope



**Count on it.**