



BATTERY CHAINSAW

60V MAX* FLEX-FORCE POWER SYSTEM™



EASY POWER.

LIGHTWEIGHT YET POWERFUL

This cordless chainsaw with 41 cm bar and chain starts easily every time and lets you cut medium logs and timber like a pro.

IDEAL FOR

SMALL - MEDIUM LOGS (UP TO 15 CM)



BUILT TO LAST

Get more power, more runtime, and longer life with the digitally controlled brushless DC motor that provides power when you need it.



PRO-STYLE CHAIN TENSIONING

Tensioning tool mounts onboard the chainsaw for quick and easy access.



GET MORE DONE

Cut through 15 cm x 15 cm timber up to 50 times on a single charge[^].

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

[^]Based on controlled laboratory testing of product, using a 2.5Ah battery to cut 15cmx15cm lumber. Run-time varies with load.

60V MAX* BATTERY CHAINSAW

| IDEAL FOR | Small to Medium Logs Up to 15cm |
|------------------------------|--|
| | 60V CHAINSAW 51845T |
| Bar Length | 41 cm (16") |
| Chain Pitch/Gauge | Pitch .375"; Gauge 1,1 mm (0.043") |
| Chain Oil Capacity | 270ml |
| Chain Tensioning | Tooled |
| Motor | Brushless 60V DC |
| Toro 60v Battery & Charger | Battery and charger sold separately |
| Cuts Per Charge [^] | Up to 50 w/ L135 Battery |
| Bar Cover | Included |
| Chain Speed | 11 m/s (36 ft/s) |
| Speed Control | Variable trigger |
| Weight | 4,4 Kg (9.6 lbs) - Bare Tool; 5,8 kg w/ L135 Battery |
| Noise Rating | Measured Sound Power: 101.1 dBA; Guaranteed Sound Power: 105 dBA; Sound Pressure: 91 dBA; Uncertainty: 3 |
| Hand/Arm Vibration | Left & Right: 5.7 m/s ² rms; Uncertainty K: 3 m/s ² |
| Comfort Grip | Standard |
| Warranty** | 3-Year Full Coverage |



GET MORE DONE

Cut through a medium sized timber up to 50 times[^] on a single charge.

EASY TO USE

Pro-style chain tensioning with on-board tool storage.



51845T WITH BATTERY

EASY TO MAINTAIN

Automatic chain oiler.



POWER ON DEMAND

Variable speed trigger drives more power when you need it.



toro.com/easypower

©2021 The Toro Company Part No. 21-530 Master

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties. toro.com

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

[^]Based on controlled laboratory testing of product, using a 2.5Ah battery to cut 15cmx15cm lumber. Run-time varies with load.

** For full warranty terms and conditions, please refer to the operator's manual on www.toro.com



facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope

