

HoverPro® Series Hover Mowers

HOVERPRO TACKLES TOUGH UNDULATIONS, STEEP SLOPES, AND BANKS WITH EASE.

The Toro HoverPro is perfect for maintaining turf on steep slopes, tight undulations, areas near water or bunker lips. A light footprint makes the HoverPro easy to operate while its rugged design ensures years of quality performance.



Nylon Wire Cutter – (HoverPro 400 & 450)



Steel Cutting Blade – (HoverPro 500 & 550)

toro.com/hoverpro

FEATURES

- HoverPro 500 and 550 feature an industry leading 14" (35.5 cm) impeller for maximum lift and smoother mowing.
- Exceptionally strong and lightweight ABS injection-molded deck
- Better control and greater stability in extreme conditions and difficult cutting areas
- High power-to-weight ratio (comparable to 2-stroke engines) thanks to weightconscious engineering.

HOVERPRO® SERIES SPECIFICATIONS*

The Toro HoverPro is perfect for maintaining turf on steep slopes, tight undulations, near water or bunker lips. A light footprint makes the HoverPro easy to operate while its rugged design ensures years of quality performance.



	HOVERPRO 400, MODEL 02615*	HOVERPRO 450, MODEL 02612*	HOVERPRO 500, MODEL 02604*	HOVERPRO 550, MODEL 02606*
ENGINE	Honda® GXV57	Honda® GCV160	Honda® GCV160	Honda® GCV160
CAPACITY	57 cc	160 cc	160 cc	160 cc
CUTTING WIDTH	16" (40 cm)	18" (46 cm)	20" (51 cm)	21" (53 cm)
CUTTING HEIGHT	0.7"- 1.2" (18 - 30 mm)	0.7"- 1.2" (18 - 30 mm)	0.6"- 1.3" (16 - 34 mm)	0.6"- 1.3" (16 - 34 mm)
NET WEIGHT	27.5 lbs (12.5 kg)	39 lbs (17.7 kg)	41.8 lbs (19 kg)	41.8 lbs (19 kg)
CUTTER SYSTEM	Nylon Wire	Nylon Wire	Steel Cutting Blade	Steel Cutting Blade
WARRANTY	Two-year limited warranty. Refer to operator's manual for further details.			

HoverPro® Series Accessories



Hi-Rise Kit - bolts to existing deck to increase height of cut by 1.4" (3.5 cm) (400 & 450 models only)



Transport Wheels - maneuver your HoverPro with less effort (450, 500, & 550 models only)



Extension Handles - makes working on slopes even easier (450 & 550 models only)

2 Rev. 1/19



Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801











facebook.com twitter.com/TheToroCompany youtube.com/ToroCompanyEurope



^{*}Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.