



## Sand Pro® 2040Z Bunker Rake

### ANOTHER INDUSTRY FIRST IN BUNKER MAINTENANCE.

The Sand Pro 2040Z mechanical groomer is unlike anything else in the marketplace—a zero-turn bunker rake delivering unmatched productivity and maneuverability.

The Sand Pro 2040Z is a daily bunker rake that will reduce your bunker maintenance labor cost. With the exclusive Flex Tooth Rake with patent-pending lift in turn technology, the 2040Z is the only mechanical groomer that can groom in a zero-turn without leaving tire marks or leaving unraked teardrops of sand. The nimble Sand Pro 2040Z will save you valuable time in your workday, improving bunkers' surface playability and consistency.



[toro.com/sandpro](https://toro.com/sandpro)

#### F E A T U R E S

- Kawasaki 12.2 hp (9.1 kW) gasoline, v-twin engine
- Flex tooth rake eliminates tire marks and mounds of sand
- Power steering via independent control sticks
- Unitized transmission minimizes hydraulic lines and connections
- Transport speed up to 12 mph (19.3 km/h)
- Hydraulic-powered groomer lift
- 2-post fixed ROPS, ISO/DIS 21299.2 certified



| SAND PRO 2040Z, MODEL 08706    |                                                                                                                                                                                                                                                                                                                                |                      |                                                     |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------------------------------------------|
| ENGINE                         | Kawasaki 2 cylinder, air cooled, gasoline engine; gross power 13.6 hp (10.1 kW), governed power 12.2 hp (9.1 kW) @ 2,400 rpm; max torque 27.3 ft-lb (37.0 N-m) @ 1,800 rpm; Displacement 36.7 in³ (603 cc); Oil capacity w/filter 1.7 qt (1.6 L) with filter and 1.5 qt (1.4 L) without filter); oil filter external, spin-on. |                      |                                                     |
| AIR CLEANER SYSTEM             | Heavy duty single stage cyclonic air filter with replacement element                                                                                                                                                                                                                                                           |                      |                                                     |
| FUEL CAPACITY                  | 4.5 gal (17 L) of unleaded gas (maximum 10% ethanol)                                                                                                                                                                                                                                                                           |                      |                                                     |
| TRACTION DRIVE                 | Belt driven independent infinitely variable unitized transmission, with automatic tensioning system.                                                                                                                                                                                                                           |                      |                                                     |
| HYDRAULIC OIL                  | Factory fill Mobil fluid 424 tractor transmission fluid; left hand transmission section: 3.1 qt (3.25 L); right hand transmission section: 3.55 qt (3.75 L)                                                                                                                                                                    |                      |                                                     |
| GROUND SPEED                   | Forward 0–12 mph (0-19.3 km/h), reverse 0–4 mph (0–6.4 km/h). See Speed Limiter Kits below for additional information.                                                                                                                                                                                                         |                      |                                                     |
| TIRES/WHEELS                   | Drive wheels 25 x 12-9, 3-ply rating pneumatic tubeless demountable with a Turf Tamer (knobby) tread. Front wheel 16 x 7.5-8 4-ply rating pneumatic tubeless demountable with turf traction tread. Recommended tire pressure: 7 psi (48 kPa) all tires.                                                                        |                      |                                                     |
| MAIN FRAME                     | Rectangular structured steel tube and high strength steel plate welded construction.                                                                                                                                                                                                                                           |                      |                                                     |
| BRAKES                         | Twin levers with dynamic braking through hydrostatic transmission. Hand actuated parking brake lever that controls two integral wet disc brakes contained within transmission.                                                                                                                                                 |                      |                                                     |
| STEERING                       | Power steering, controlled through two independent control sticks with integrated dampeners. Min. turning radius: 0" (0 cm)                                                                                                                                                                                                    |                      |                                                     |
| CONTROLS/GAUGES                | Ignition: off/run/start; throttle: low-high idle; choke: open/closes choke plate; parking brake: off-on.<br>LCD logic cluster includes hour meter and safety interlocks for operator presence, neutral and parking brake.                                                                                                      |                      |                                                     |
| REAR ATTACHMENT HYDRAULIC LIFT | Raise/lower switch mounted at end of right handle.                                                                                                                                                                                                                                                                             |                      |                                                     |
| SEAT                           | High back cushion vinyl seat with drain hole, integrated armrest and retractable seat belt; adjustment is 10.2 cm (4") fore and aft.                                                                                                                                                                                           |                      |                                                     |
| ROPS                           | Two post fixed ROPS, certified per ISO/DIS 21299.2 specifications                                                                                                                                                                                                                                                              |                      |                                                     |
| STORAGE                        | Built-in cup holder, rake holder and personal storage reached from seat.                                                                                                                                                                                                                                                       |                      |                                                     |
| ELECTRICAL FEATURES            | 12 V system, 20 A alternator at 3,600 rpm. Battery voltage is displayed when key switch is moved from off to run (low battery LED will illuminate if key voltage is less than 12.3 V in run position)                                                                                                                          |                      |                                                     |
| SOUND LEVEL                    | 88 dBA (operator ear)                                                                                                                                                                                                                                                                                                          |                      |                                                     |
| DIMENSIONS/WEIGHT              |                                                                                                                                                                                                                                                                                                                                | with Flex Tooth Rake | with Nail Drag                                      |
|                                | Length:                                                                                                                                                                                                                                                                                                                        | 89" (226 cm)         | 84.8" (215 cm)                                      |
|                                | Width:                                                                                                                                                                                                                                                                                                                         | 84" (213 cm)         | 71.5" (182 cm)                                      |
|                                | Overall Height:                                                                                                                                                                                                                                                                                                                | 73" (185 cm)         | 73" (185 cm)                                        |
|                                | Weight:                                                                                                                                                                                                                                                                                                                        | 920 lbs. (417 kg)    | 970 lbs. (439 kg)                                   |
|                                |                                                                                                                                                                                                                                                                                                                                |                      | Wheelbase: 58" (147 cm)                             |
|                                |                                                                                                                                                                                                                                                                                                                                |                      | Tread width (to centerline of tire): 46.9" (119 cm) |
| GROUND CLEARANCE               | 5.5" (14 cm) at machine centerline 24" (61 cm) tire                                                                                                                                                                                                                                                                            |                      |                                                     |
| TIE DOWNS                      | Four loops, one located on each corner of the machine.                                                                                                                                                                                                                                                                         |                      |                                                     |
| WARRANTY                       | 2-year warranty. Refer to the Operator's Manual for further details.                                                                                                                                                                                                                                                           |                      |                                                     |
| SAFETY CERTIFICATIONS          | Certified to meet ANSI specification B71.4 - 2012 standards when equipped with weight kits supplied with attachments. Certified to meet ISO/DIS 21299 for ROPS. Engine meets all applicable emission standards per the manufacturer. Certified to meet C-Tick 2004/108/EC/(EMC) and the CE Machinery Directive.                |                      |                                                     |

| REAR ATTACHMENTS (NOTE: Unit must always have a rear attachment installed to meet ANSI and CE specifications) |                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>FLEX TOOTH RAKE (08716) (GOLF APPLICATIONS)</b>                                                            | <ul style="list-style-type: none"> <li>84" (213 cm) wide tooth rake with three reversible rubber trowels that will not tear bunker liners</li> <li>Convex Trowel Design is able to continuously groom a 70" (178 cm) radius surface</li> <li>Lift-in-turn design allows for continuous grooming during a zero radius turn</li> <li>Rubber trowel design reduces damage to bunker edges and liners</li> </ul> |
| <b>BROOM FINISHING KIT (08719)</b>                                                                            | Three section brush                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>NAIL DRAG (08717) (INFIELD GROOMING APPLICATIONS)</b>                                                      | <ul style="list-style-type: none"> <li>66" (168 cm) wide with 88 removable nails arranged in diamond pattern</li> <li>3 height position for nails increases material flow and extends nail wear</li> <li>71.5" (182 cm) rubber groomer</li> <li>Back blade allows for moderate or small area leveling of infield surface</li> </ul>                                                                          |
| <b>DRAG MAT FINISHING KIT (08718)</b>                                                                         | 78" W X 18" L x 1" (198 W x 45.7 L x 2.5 cm) square steel mat; includes cradles to store mat during transport.                                                                                                                                                                                                                                                                                               |
| OTHER TRACTION UNIT ACCESSORIES                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>LIGHT KIT (08721)</b>                                                                                      | 2 LED lights, one in front one mounts to ROPS and points rearward. 3 Position switch, all lights on, front on or off.                                                                                                                                                                                                                                                                                        |
| <b>SPEED LIMITER KIT (08720)</b>                                                                              | Automatically reduces maximum speed of the traction unit when the rear attachment is lowered. Adjustable to maximum speed of 3–7 mph (4.8–11.3 km/h).                                                                                                                                                                                                                                                        |
| <b>TRANSPORT SPEED LIMITER KIT</b>                                                                            | Reduces speed infinitely from top speed to approximately 7 mph (11 km/h) or top speed of grooming speed. Part 130-7877                                                                                                                                                                                                                                                                                       |
| <b>SEAT SUSPENSION KIT</b>                                                                                    | Rubber isolators provide cushioning. PN 125-6469                                                                                                                                                                                                                                                                                                                                                             |
| <b>MESH BAG KIT</b>                                                                                           | Storage bag for maintenance tools, trash, debris, etc.; mounts to ROPS. PN 127-0359                                                                                                                                                                                                                                                                                                                          |
| <b>TURF TRAC TIRE</b>                                                                                         | Less aggressive tread for rear drive tires. PN 125-6462                                                                                                                                                                                                                                                                                                                                                      |
| <b>BIMINI SUNSHADE (30358)</b>                                                                                | Canvas sunshade that mounts to ROPS.                                                                                                                                                                                                                                                                                                                                                                         |
| <b>RAKE HOLDER</b>                                                                                            | SP2040Z has a standard rake holder mounted on left hand side, a second optional rake holder can mount to right hand side of SP2040Z. PN 130-7876                                                                                                                                                                                                                                                             |

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Rev. 3/26

2

The Sand Pro 2020 is manufactured in Tomah, WI ISO 9002 Certified Plant.



## toro.com

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801  
Fax: (1) 952 887 8258

©2026 The Toro Company.  
All Rights Reserved.  
26-149-master



facebook.com  
youtube.com/ToroCompanyEurope  
x.com/TheToroCompany



Count on it.