



Workman® MDX Series Utility Vehicles

DO MORE...WITH MORE.

The Workman MDX Series with SRQ™ combines a coil-over shock absorber suspension design with an Active In-Frame™ twister joint. These features deliver superior ride quality for optimum operator comfort and control. The hefty payload capacity and four-wheel hydraulic brakes enhance productivity to tackle the toughest jobs. The Workman MDX has the power and versatility to help you do more, with more!



[toro.com](https://www.toro.com)

FEATURES

More Power

- A 480 cc petrol or a 600 cc diesel engine powers the MDX to an impressive 567 kg cargo capacity and 544 kg towing capacity. This vehicle is built to haul your toughest load to any jobsite and features hydraulic brakes on all four wheels to safely stop you when you get there.

More Comfort

- The SRQ suspension boasts an independent A-frame front suspension with coil over shock absorbers, proprietary active in-frame twister joint and a rear suspension featuring a swing arm design with coil-over shock absorbers. The result is a smooth ride that you and your team will notice immediately. Operators suffer less fatigue and stay more productive throughout the day.

More Control

- An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and move throughout your property more safely.

More Durable

- Virtually unbreakable exterior components make the Workman MDX more durable and dependable. This vehicle is built to work as hard as you do, year after year.

More Accessories

- A deluxe hard cab, canopy and windscreen provide protection from the sun or the elements. The roll-over protective structure (ROPS), brush guard, and optional all-terrain tyres help you operate in more challenging terrain. Add the deluxe portable refreshment centre to turn your Workman into a revenue-producing machine.

	WORKMAN MDX MODEL 07235TC	WORKMAN MDX-D MODEL 07236TC
ENGINE	480 cc, air-cooled, two-cylinder, Briggs & Stratton® Vanguard®. Meets 2011 EPA & CARB exhaust and evaporative emissions regulations.	600 cc, liquid-cooled, 2-cylinder, Kubota® diesel. Biodiesel ready for use up to B-20 (20% biodiesel and 80% petroleum blend).
SRQ™ SYSTEM	Active In-Frame™ twister pivot joint, front and rear suspension.	
FRONT SUSPENSION	Modified MacPherson strut, adjustable coil over shock absorbers.	
REAR SUSPENSION	Trailing arm with adjustable coil over shock absorbers.	
GROUND SPEED	16 mph governed. Optional 20 mph requires ROPS and seat belts.	
BRAKES	Front wheel hydraulic disc. Rear wheel hydraulic drum.	
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 35 cm (13.75") diameter.	
FRAME	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat. Body and bed constructed of dent and corrosion-resistant polyethylene.	
GROUND CLEARANCE	Front: 25.4 cm (10"), Rear: 18 cm (7")	
TYRES	Front: 22 x 9.50-10, 4-ply. Rear: 24 x 12.00-10, 4-ply. Optional all-terrain tyres	
FUEL CAPACITY	24.6 l	
DIMENSIONS	Width 155.4 cm (61.2")	Length 307.5 cm (121.1")
CAB DIMENSIONS INSTALLED	Height 201.1 cm (79.2")	Width 162.5 cm (64")
CANOPY DIMENSIONS INSTALLED	Height 201.9 cm (79.5")	Width 155.4 cm (61.2")
TURNING CLEARANCE CIRCLE	Inside rear tyre: 221 cm (87"), outside front tyre: 653 cm (257").	
INSTRUMENTATION	Hour meter, low oil pressure warning light, accessory power port. Dash has 2 cup-holders, radio holder and glovebox storage.	Hour meter, oil pressure, glow plug, coolant temperature, battery charge indicator lights and accessory power port. Dash has 2 cup-holders, radio holder and glovebox storage.
STARTING	Pedal start (optional key start)	Key start
CARGO BED SIZE INTERNAL	Length: 113 cm (44.5"). Width: 125 cm (49"). Height: 26 cm (10.25"). LLDPE resin.	
TOTAL VEHICLE CAPACITY	750 kg	
CARGO BED PAYLOAD CAPACITY	567 kg	
TRAILER TOWING CAPACITY	182 kg trailer, 23 kg tongue weight with standard hitch. 544 kg trailer, 45 kg tongue weight with heavy-duty tow hitch.	
OPTIONAL ACCESSORIES	Canopy, solid folding windscreen, electric bed lift, brush guard, ROPS, brake/rear/signal light kit, receiver hitch, BOSS® plow, beverage cart.	
WARRANTY	Two-year or 1,500 hour warranty. Refer to the Operator's Manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801

©2025 The Toro Company.
All Rights Reserved.
25-160-GB



facebook.com
youtube.com/ToroCompanyEurope
x.com/TheToroCompany

