



Workman® MDX Lithium

UTILITY VEHICLES

TAKE CHARGE OF YOUR WORKDAY.

For decades, the Toro Workman lineup has set the standard for tough and hard-working utility vehicles. Toro is proud to continue this legacy of performance with the all-new Workman MDX Lithium.

This lithium-powered MDX comes with same payload capacity, trailer-towing capacity and comfortable ride that you have come to know in our petrol and diesel-powered Workman MDX.



toro.com

FEATURES

Toro Hypercell® batteries

- The lithium-powered MDX utilises Toro's patent-pending lithium-ion Hypercell batteries that provide extended battery power for consistent performance over the life of the vehicle. The MDX Lithium quickly charges overnight, keeping you running all day long.

Superior comfort & control

- The proprietary SRQ™ (Superior Ride Quality) suspension creates a smooth ride and reduces rider fatigue, allowing your team to stay more productive throughout the day.
- MDX comes standard with an automotive-grade rack and pinion steering system, providing more control and lower steering effort. This allows operators to focus on the task at hand and move throughout your property more safely.

Parking convenience

- The electronically-controlled parking brake seamlessly activates once the vehicle comes to a stop and deactivates when the driver presses the pedal.

Commercial grade durability

- Virtually unbreakable exterior components make the Workman MDX Lithium more durable and dependable. This vehicle is built to work as hard as you do, year after year.



	WORKMAN MDX LITHIUM, MODEL 08303/08303TC
POWER SOURCE	Lithium-ion batteries with integrated Battery Management System (BMS)
ENERGY CAPACITY	8.64 kWh, 55 V nominal; 63 V max
CHARGER	On-board high efficiency 1,200 W smart charger. -AC input voltage 100–240 VAC -AC input frequency 50/60 Hz -Max input current 13.4 A
SRQ™ SYSTEM	Active In-Frame™ twister pivot joint, front and rear suspension.
FRONT SUSPENSION	Modified MacPherson strut, adjustable coil-over shock absorbers.
REAR SUSPENSION	Trailing arm with adjustable coil-over shock absorbers.
GROUND SPEED	16 mph standard, adjustable from 5–19 mph
BRAKES	All-wheel hydraulic disc brakes. Integrated automatic parking brake.
STEERING	Rack and pinion steering system with ergonomic steering wheel that includes an integrated clip.
FRAME	Welded steel channel and tube in body construction. Frame surfaces are dipped e-coat and powder coat finished. Body and bed constructed of dent- and corrosion-resistant polyethylene.
GROUND CLEARANCE	Front: 25.4 cm (10"), Rear: 18 cm (7")
TYRES	Front: 22 x 9.50-10, 4-ply, Rear: 24 x 12.00-10, 4-ply. Mounted on custom aluminium rims.
DIMENSIONS	Length/width 307.3 cm (121")/155 cm (61"). Wheel base 205.7 cm (81")
CANOPY DIMENSIONS INSTALLED	Height/width: 201.9 cm (79.5")/155.4 cm (61.2")
TURNING CLEARANCE CIRCLE	Inside rear tyre: 221 cm (87"), outside front tyre: 653 cm (257")
INSTRUMENTATION	Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch. Two cup-holders, radio holder, in-dash storage compartments, speedometer, gear indicator, estimated charge time and diagnostic/fault codes.
STARTING	Pedal start
CARGO BED SIZE INTERNAL	Length: 113 cm (44.5"), width: 125 cm (49"), height: 26 cm (10.25"), LLDPE resin
TOTAL VEHICLE CAPACITY	750 kg
CARGO BED PAYLOAD CAPACITY	567 kg
TRAILER TOWING CAPACITY	182 kg trailer, 23 kg tongue weight with standard hitch. 544 kg trailer, 45 kg tongue weight with heavy-duty tow hitch
OPTIONAL ACCESSORIES	Canopy, windscreen, electric bed lift, brush guard, ROPS, brake/rear/indicator light kit, receiver hitch, beverage cart.
WARRANTY	Two-year or 1,500-hour warranty. Lithium-ion battery five years. Refer to the Operator's Manual for further details

Power to get the job done.

Toro's proprietary HyperCell® battery system was specifically developed to meet customer demand and is optimised to deliver exceptional continuous runtime, allowing it to run as long as your crew. At the end of a long workday, the on-board charger conveniently plugs into a standard wall socket and fully charges the vehicle overnight.



*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Rev. 11/25

The Workman MDX is manufactured in Tomah, WI ISO 9002 certified plant.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

©2025 The Toro Company.
All rights reserved.
25-159-GB



facebook.com
youtube.com/ToroCompanyEurope
x.com/TheToroCompany



Count on it.