

TORO[®]

Z MASTER[®] PROFESSIONAL
7000 SERIES



- ✓ **POWER THROUGH** the toughest conditions with the high-torque 3-cylinder diesel engine.
- ✓ **RESIST DAMAGE** from debris with the rugged deck made of 7-gauge, high-strength steel.
- ✓ **USE BIODIESEL** fuel blends with the compatible fuel pump, fuel filter and fuel lines.
- ✓ **SURVIVE IMPACTS** that could destroy lesser spindles with Toro's robust spindle assemblies.
- ✓ **SAVE DOWNTIME** with flat-free, semipneumatic caster tyres.
- ✓ **REDUCE OPERATOR FATIGUE** with a thick, cushioned, deluxe suspension seat that absorbs vibrations.



7000 SERIES	74279TE REAR	74264TE SIDE	74265TE SIDE
CUTTING WIDTH	132 cm	132 cm	▶ 152 cm
DEFLECTOR WIDTH	173 cm	173 cm	▶ 193 cm
ENGINE	23 hp (16.6kW) Kubota®, Diesel	23 hp (16.6kW) Kubota, Diesel	23 hp (16.6kW) Kubota, Diesel
GROUND SPEED	0-18 km/h	0-18 km/h	0-18 km/h
DECK TYPE	TURBO FORCE Rear Discharge	TURBO FORCE Side Discharge	TURBO FORCE Side Discharge
DECK HEIGHT	140 mm	140 mm	140 mm
HOC	38-127 mm	38-127 mm	38-127 mm
SPINDLE BEARINGS	Sealed	Sealed	Sealed
DRIVE TYRES	58 x 24-30.5 4-ply	58 x 24-30.5 4-ply	58 x 30-30.5 4-ply
CASTER TYRES	33 x 16.5 - 15 Flat-free Semi-Pneumatic	33 x 16.5 - 15 Flat-free Semi-Pneumatic	33 x 16.5 - 15 Flat-free Semi-Pneumatic
FUEL/CAPACITY	Diesel/ 45 litres	Diesel/ 45 litres	Diesel/ 45 litres
WEIGHT	733 kg	733 kg	722 kg

▶ = Enhanced or step-up feature



TURBO FORCE® DECK

Works with the high-torque diesel engine for outstanding results at higher ground speeds.



DIESEL ENGINES

Lower fuel consumption and are more efficient than comparable petrol engines. Diesel fuel also contains about 18% more energy by volume for extra power.



LIQUID-COOLED ENGINE SYSTEM

Extends engine life with cleaner combustion. Plus, a well-balanced engine keeps vibration to a minimum.



BIODIESEL READY ENGINES

Accept up to 20% biodiesel (B20) fuel blends, which can cut emissions nearly in half vs. traditional diesel fuel (based on EPA-designed engine tests)

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.

toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

Printed in U.S.A.
©2016 The Toro Company.
All Rights Reserved.
200-6476



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.