

**TORO**

# Workman® GTX Series

## Utility Vehicles

## SIMPLY SUPERIOR

The Workman GTX is a grounds and turf crossover vehicle that boasts an unequalled combination of comfort, utility and control, making it simply superior to the competition. Its increased power, improved steering and exclusive suspension and braking systems make the Workman GTX the most versatile, practical and comfortable utility vehicle in its class. Available in petrol or electric, the Workman GTX features hundreds of configuration options; including front and rear attachments, a flat bed and a four-seat option. So whether you are setting cups, checking on irrigation, working around campus, or moving people or materials, the Workman GTX has the power and versatility to get the job done right.



[toro.com/gtx](https://toro.com/gtx)

## F E A T U R E S

### Power

Whether you choose the 429 cc EFI petrol, 48 V A/C electric or lithium-ion Workman GTX, power and performance come standard. An improved power to weight ratio boosts payload capacity and productivity by allowing you to do more, every day!

### Steering

An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.

### Suspension

Coil-over shocks all around the vehicle deliver greater suspension travel and adjustability resulting in a smoother ride and minimised operator fatigue.

### Versatility

The Workman GTX is adaptable for any task. Two or four-seat configurations come with bench or bucket seats. Front and rear attachment points free up the bed for more hauling capacity. 1.2 m and 1.8 m (4 and 6-ft) flat beds are also available.

### Hydraulic disc brakes

Minimal maintenance, no cable adjustment and less pedal force than mechanical/cable brakes affords the Workman GTX reliable and consistent stopping power.

### Durability

Virtually unbreakable composite exterior components and a powder coated frame and underbody give the Workman GTX superior durability. Run it hard, day after day.



**WORKMAN® GTX SERIES SPECIFICATIONS\***

	WORKMAN GTX (PETROL EFI) MODELS 07409, 07059TC, 07411EX	WORKMAN GTX LIFTED (PETROL EFI) MODEL 07059LT	WORKMAN GTX (ELECTRIC) MODELS 07410, 07131TC, 07412EX		
<b>POWER SYSTEM</b>	429 cc, air-cooled, single cylinder Kohler® EFI petrol engine. Meets current EPA, CARB and Stage V exhaust and evaporative emissions regulations.		48 V brushless AC induction drive.		
<b>STEERING</b>	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 35 cm (13.75") diameter.				
<b>TURNING RADIUS</b>	<b>Standard model:</b> turning clearance circle: 20.7' (6.3 m), inside turning radius: 60.25" (153 cm). <b>Extended model:</b> turning clearance circle: 31' (9.45 m), inside turning radius: 100" (254 cm).				
<b>BRAKES</b>	Front and rear wheel hydraulic disc brakes.				
<b>SUSPENSION</b>	Front: modified macpherson strut. Rear: articulating swing arm. Adjustable coil over shocks at all four wheels.				
<b>SUSPENSION TRAVEL</b>	Front suspension travel: 8.9 cm (3.5"). Rear suspension travel: 10.2 cm (4").				
<b>FUEL CAPACITY</b>	18.9 L		N/A		
<b>GROUND SPEED</b>	16 mph governed. Speed reduction kits available.		16 mph, adjustable.		
<b>TRANSAXLE</b>	11.47:1 forward, 14.35:1 reverse	11.47:1 forward, 14.35:1 reverse	17:1 double-reduction high torque.		
<b>GROUND CLEARANCE</b>	Front: 22.8 cm (9"). Rear: 15.2 cm (6").	Front: 30.4 cm (12"). Rear: 17.8 cm (7").	Front: 22.8 cm (9"). Rear: 15.2 cm (6").		
<b>TYRES</b>	20 x 8.00-10, 4-ply. Or alternate 4-ply/6-ply.		20 x 8.00-10, 4-ply. Or alternate 4-ply/6-ply.		
<b>WHEELS</b>	25.4 cm (10") steel.	30.5 cm (12") aluminum.	25.4 cm (10") steel.		
<b>BATTERIES</b>	One 12 V starter battery.		Eight Trojan® T-125 advanced deep cycle 6 V batteries featuring a single port fill system and water level indicators.		
<b>CONTROLLER</b>	N/A		540 A max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.		
<b>CHARGER</b>	N/A		On-board high efficiency 1 kW smart charger with 85-265 VAC global input, temperature controlled, sealed and waterproof, remote indicator viewable at charge port.		
<b>ELECTRIC MOTOR</b>	N/A		Brushless high-torque AC Induction motor with 5.0 kW continuous power.		
<b>INSTRUMENTS/DASH</b>	Hour meter, fuel gauge, USB power port, headlight switch, on/off ignition key switch, horn, gear selector and parking brake lever. Two cup-holders, radio holder and three in-dash storage compartments.		Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch, gear selector and parking brake lever. Two cup-holders, radio holder and three in-dash storage compartments.		
<b>STARTING</b>	Pedal or key start capability standard.		Pedal start.		
<b>DIMENSIONS</b>	<b>Vehicle configuration</b>	<b>Width</b>	<b>Length</b>	<b>Height</b>	<b>Wheel base</b>
	2-seat with bed (GTX std.)	119.3 cm (47")	302 cm (119")	127 cm (50.2")	197 cm (77.8")
	2-seat with bed (GTX lifted)	119.3 cm (47")	302 cm (119")	135 cm (53.2")	197 cm (77.8")
	4-seat with bed (GTX std.)	119.3 cm (47")	366 cm (144")	127 cm (50.2")	290 cm (114")
	2-seat with 1.8 m (6') flat bed (GTX std.)	119.3 cm (47")	396 cm (156")	127 cm (50.2")	290 cm (114")
<b>CAB DIMENSIONS INSTALLED</b>	<b>Height:</b> 201 cm (79") <b>Width:</b> 142 cm (56")	<b>Height:</b> 208 cm (82") <b>Width:</b> 142 cm (56")	<b>Height:</b> 201 cm (79") <b>Width:</b> 142 cm (56")		
<b>CANOPY DIMENSIONS INSTALLED</b>	<b>Height:</b> 191 cm (75.2") <b>Width:</b> 138 cm (54.3")	<b>Height:</b> 199 cm (78.2") <b>Width:</b> 138 cm (54.3")	<b>Height:</b> 191 cm (75.2") <b>Width:</b> 138 cm (54.3")		
<b>WEIGHT</b>	<b>Vehicle configuration</b>	<b>Weight</b>	<b>Vehicle configuration</b>	<b>Weight</b>	
	2-seat with bed	397 kg	2-seat with bed	633 kg	
	4-seat with bed	522 kg	4-seat with bed	757 kg	
	2-seat with 1.8 m (6') flat bed	573 kg	2-seat with 1.8 m (6') flat bed	809 kg	
<b>CARGO BED</b>	<b>Width</b>	<b>Length</b>	<b>Height</b>	<b>Capacity</b>	
	97.8 cm (38.5")	101.6 cm (40")	27.9 cm (11")	363 kg	
<b>VEHICLE CAPACITY</b>	2-seat with bed 544 kg				
<b>TOWING CAPACITY</b>	680 kg Class 1 – 1.25" (32 mm) receiver standard.				
<b>OPTIONAL ACCESSORIES</b>	Canopy, folding windscreen, 4-seat configuration, flat bed, 1.8 m (6-foot) flat bed, bed sides, storage box, rubbish bin mount, bed racking, electric bed lift, brush guard, 12 V outlet, brake/rear/indicator lights, ROPS certified hard cab, horn kit, reversing alarm kit, parking brake alarm kit, all-terrain tyre kit, 2-post ROPS kit, beverage cart, range cage, glass windscreen, medical bed.				
<b>WARRANTY</b>	Two-year or 1,500 hour warranty. Three-year engine warranty. Refer to the Operator's manual for further details.				

\* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

Rev. 2/25

The Workman GTX is manufactured in Windom, MN ISO 9002 certified plant.



**toro.com**

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801

©2025 The Toro Company.  
All Rights Reserved.  
25-156-GB



facebook.com  
youtube.com/ToroCompanyEurope  
x.com/TheToroCompany



**Count on it.**